



Data/Specification Sheet

Features

- Meets or exceeds requirements of UL Standard 8 and Standard 711
- Meets requirements of NFPA 10
- Simple operation and maintenance
- Wide angle, soft discharge spray pattern
- Stainless steel bourdon tube gauge
- Trilingual, glare resistant, one piece, mylar nameplate with barcode
- Rechargeable
- Sold and serviced through a network of independent distributors
- UL/ULC rated 2-A:K
- Stainless steel valve assembly, ring pin, and pick-up tube with polymeric strainer
- USCG approved with proper bracket
- Pre-filled with 1.6 Gallons (6 L) ANSULEX Low ph Wet Chemical Recharge Agent and pressurized at the factory for convenient service – ready to use – right out of the box

APPLICATIONS

The ProTex II® Model K01-3 Wet Chemical Fire Extinguisher is specifically designed for use on fires that involve combustible cooking vegetable or animal fats in commercial cooking equipment. Typical appliances include: fryers; griddles; range tops; upright, natural charcoal, or chain-type broilers; electric, lava rock, mesquite, or gas radiant char-broilers; and woks.

More efficient cooking appliances, plus the use of non-saturated cooking oils, require a fire extinguishing agent which will not only smother a fire but provide a cooling effect.

The extinguisher is ideally suitable for use in restaurants, hospitals, nursing homes, hotels, schools, airports, and other similar facilities.

It is used as a backup to an automatic fire suppression system.

The energy source to the cooking equipment shall be shut off by the automatic fire suppression system to assist in the suppression process and permit the cooking media to cool below its auto-ignition temperature.

DESCRIPTION

The ProTex II® extinguisher is an attractive, easy to use and maintain, stainless steel extinguisher that will match commercial kitchen decor.

The ANSULEX Low ph Wet Chemical Recharge Agent used in the extinguisher is a specially-formulated aqueous solution. It has been developed to provide rapid flame suppression and securement of hot fuels such as cooking shortenings.



CODES

Meets Class K (Combustible Cooking Media) fire requirements of NFPA 10.

SPECIFICATIONS

- Model K01-3
- UL/ULC Rating 2-A:K
- Capacity 1.6 gal (6 L) ANSULEX Low ph Wet Chemical Recharge Agent
- Extinguisher Dimensions:
 - Height 21.25 in.
 - Width 9.5 in.
 - Diameter 7 in.
- Shipping Weight: 25 lbs.
- Range: 8-10 ft.
- Discharge Time: Approximately 45 seconds
- Temperature Range: -20°F to 120°F (-29°C to 49 °C)
- Bracket: 30937AS USCG Approved

ORDERING INFORMATION

Part No. 453111 ProTex II® Wet Chemical Fire Extinguisher

Part No. 451410 ANSULEX Low ph Wet Chemical Recharge Agent -
1.6 gal (6 L)

Safety Data Sheets (SDS) are available at www.heiserusa.com

Copyright © 2024 Heiser Logistics. All rights reserved.

ProTex II®, and the product names listed in this material are marks and/or registered marks. Unauthorized use is strictly prohibited.