

25-40 amp contactors millennium series

These new ACC Millennium Series Contactors offers high performance as well as flexibility and reliability. It is designed to match numerous applications such as: motors, power supplies, food service equipment, compressors, business machines, resistive heating, air conditioning, refrigeration equipment and welding. The Millennium Series Contactors feature a manual test button which directly closes movable contacts without energizing the coil.

specifications:

- ARI 780 rated
- Quick connects: double .250 standard
- Coil termination: 6-32 screw & single QC
- Temperature range: -40°C to 65°C / -40°F to 150°F
- Contact material: silver cadmium oxide
- Approximate mechanical life cycles: 1,000, 000
- 25 and 30 amp models are standard with arc covers and QC terminals
- 40 amp models are standard with lugs and QC terminals
- Dimensions , Coil Data, Horsepower & Accessories see page C-17

U.L. 508 GUIDE NO. NLDX2 / FILE NO. E75492

C.S.A. C22.2 NO. 14 / FILE NO. LR49598

2 and 3 pole contactors, w/ molded encapsulated coils

MARS NO.	AH MODEL NO.	COIL VOLTS 50/60 HZ	POLES	FLA 600V	LOCKED ROTOR AMPS			RES AMPS PER POLE 600V
					240V	480V	600V	
60505	ACC238UMM10	24	3	25	150	125	100	35
60506	ACC238UMM20	110/120	3	25	150	125	100	35
60507	ACC238UMM30	208/240	3	25	150	125	100	35
60508	ACC238UMM50	277	3	25	150	125	100	35
60509	ACC238UMM60	480	3	25	150	125	100	35
60510	ACC328UMM10	24	2	30	180	150	120	40
60511	ACC328UMM20	110/120	2	30	180	150	120	40
60512	ACC328UMM30	208/240	2	30	180	150	120	40
60513	ACC328UMM50	277	2	30	180	150	120	40
60514	ACC328UMM60	480	2	30	180	150	120	40
60515	ACC338UMM10	24	3	30	180	150	120	40
60516	ACC338UMM20	110/120	3	30	180	150	120	40
60517	ACC338UMM30	208/240	3	30	180	150	120	40
60518	ACC338UMM50	277	3	30	180	150	120	40
60519	ACC338UMM60	480	3	30	180	150	120	40
60525	ACC428UMM10	24	2	40	240	200	160	50
60526	ACC428UMM20	110/120	2	40	240	200	160	50
60527	ACC428UMM30	208/240	2	40	240	200	160	50
60528	ACC428UMM50	277	2	40	240	200	160	50
60529	ACC428UMM60	480	2	40	240	200	160	50
60530	ACC438UMM10	24	3	40	240	200	160	50
60531	ACC438UMM20	110/120	3	40	240	200	160	50
60532	ACC438UMM30	208/240	3	40	240	200	160	50
60533	ACC438UMM50	277	3	40	240	200	160	50
60534	ACC438UMM60	480	3	40	240	200	160	50