

Amprobe DM73C Pen Probe Style Digital Multimeter

600V AC and 600 V DC Ranges
Improved DC Basic Accuracy 0.5%
Resistance To 34MΩ
Continuity Beeper
3400-Count Digital Display Plus Analog Bar graph
Auto Power Off
UL 3111-1 Listed
3 3/4 Digit LCD Display



Amprobe DM73C Shown



Specifications		
DC Voltage	Ranges	340 mV, 3.4, 34, 340 V, 600 V
	Accuracy	± (0.5 % rdg + 2 dgt)
	Resolution	0.1 mV in 3.4 V range
	Input Impedance	340 mV range: >100 MΩ Other ranges: 10 MΩ
AC Voltage (50-500 Hz)	Ranges	3.4 V, 34, 340, 600 V
	Accuracy	± (1.5 % rdg + 8 dgt)
	Resolution	0.1 mV in 3.4 V range
	Input Impedance	10 MΩ
Resistance	Ranges	340 Ω, 3.4, 34, 340 kΩ, 3.4, 34 MΩ
	Accuracy	340 Ω- 340 kΩ: ±(1.0 % rdg + 4 dgt) 3.4 MΩ: ±(1.5 % rdg + 4 dgt) 34 MΩ: ±(3.0 % rdg + 5 dgt)
	Max. Open Circuit Voltage	340Ω range: - 1.2 V All others: - 0.45 V
Diode Test	Range	3.4V
	Accuracy	± (2.0 % rdg + 3 dgt)
	Short Circuit Current	1.0 mA
	Max Open Circuit Voltage	3.0 VDC
	Audible Indication	< 0.2 V
Continuity Test	Display Response	< 0.5 s
	Continuity Threshold	≤ 35 Ω
Overload Protection	DC And AC Voltage	600 VDC or AC RMS
	Resistance/Continuity/Diode	All Ranges 600VDC Or VAC RMS