Miller DuraFlex® E552

Stretchable Harness

SP152 Rev. B

Materials

Webbing (DuraFlex).....Polyester

Urethane Elastomer

Minimum Tensile......5000 lbs. on webbing

Thread:.....6 cord bonded 3 strand polyester

thread. Minimum tensile of 42 lbs.

Grommets......Brass

Hardware.....Steel Minimum Tensile strength

D-Rings......5000 lbs. (22kN) Buckles......4000 lbs. (18kN)

* All hardware meets ASTM (50) fifty-hour salt spray test requirements.

Technical

Max Working Load:..... 400 lbs -181.4 kg

Identification

Label Pack..... Evoprene, Nylon

Harness Description Keys Webbing

D = DuraFlex Stretchable Webbing

DP = DuraFlex Python Webbing

K = Kevlar Webbing

P = Polyester Webbing **D-Rings**

B = Sliding Back D-Ring

FD = Front D-Ring

H = Shoulder D-Rings

S = Side Positioning D-Rings

W = Sliding Back web D-Ring

X = D-Ring Web Extension

Special Features

AB = Attached Waist Belt

AL = Adjustable Belt Loops

BL = Belt Loops

BP = Back Pad

HP = Shoulder Pads

LP = Leg Pads

LR = Lanyard Ring

RB = Removable Waist Belt

SP = Sub-Pelvic Strap

SR = Self Rescue Loops

SS = Saddle Seat


TO = Tool Belt Buckles

Shoulder/Leg Buckles

FB = Friction Buckles

MB = Mating Buckles

TB = Tongue Buckles





		Web		Shoulder	Leg	Chest	Special	
I	Model No.	Type	D-Rings	Straps	Straps	Strap	Features	Weight
E	552	D	B, FD, S	MB	MB	MB	LR	3.84 lbs. (1.7 kg)



Toll Free 800.873.5242 • Phone 814.432.2118 • Fax 800.892.4078 • www.millerfallprotection.com

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM MILLER FALL PROTECTION AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA, IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. MILLER FALL PROTECTION RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.