

MRI Stored Pressure Hand Portable

Non-Magnetic ABC Dry Chemical



For fire protection in vicinity of MRI rooms

The Non-Magnetic single-use ABC Multipurpose Dry Chemical Fire Extinguisher is manufactured using special components. Under NFPA 10 requirements stored pressure disposable models do not require six year internal maintenance examinations. It has been independently tested and received the MR Conditional Rating. The rating recognizes this extinguisher has been tested in a 7-Tesla MR imaging system and was found to pose no magnetic safety hazards.

Model XL5 MR extinguisher markings conform to new FDA recommendations contained in ASTM-2503-05 "Standard for Marking Medical Devices and Other Items for Safety in Magnetic Resonance Environments."

MRI Model XL5 MR offers single-use compliance fire protection for occupancy areas outside magnetic resonance imaging suites.

Features:

- Suitable for use on most common fires
- Easy-to-pull non-magnetic pull ring
- Tough impact-resistant non-magnetic valve, handle & lever
- Easy-to-read pressure gauge tells you extinguisher is charged and ready for use
- Six year limited warranty
- Clean white powder-coated seamless aluminum cylinder for corrosion protection
- UL Listed and UL rated 3-A:40-B:C



Badger Fire Protection
8767 Seminole Trail, Suite 202, Ruckersville, VA 22968
Tel.: 434.964.3200 • Fax: 434.964.3202 • www.badgerfire.com

Technical Data:

MRI ABC Dry Chemical Stored Pressure Extinguisher

MODEL	XL5 MR
PART NUMBER	21005726N
CAPACITY (lb.)	5.5
CAPACITY (kg)	2.27
UL FIRE RATING	3-A:40-B:C
AGENT TYPE	Multipurpose ABC
CYLINDER MATERIAL	Aluminum
VALVE MATERIAL	Aluminum
HANDLE/LEVER MATERIAL	Aluminum
EXPELLANT	Nitrogen
Operating Pressure @ 70° F	195
TEMPERATURE RANGE (° F)	-40 to 120
TEMPERATURE RANGE (° C)	-40.0 to 48.9
AGENT FLOW RATE (lb/sec)	n/a
AGENT FLOW RATE (kg/sec)	n/a
NOM. DISCHARGE TIME (sec)	13 to 15
DISCHARGE RANGE (ft.)	12 to 18
DISCHARGE RANGE (m)	3.6 to 4.6
UNIT HEIGHT (in.)	16.07
UNIT HEIGHT (cm)	40.8
UNIT WIDTH (in.)	7.5
UNIT WIDTH (cm)	19.05
UNIT DEPTH (in.)	4.5
UNIT DEPTH (cm)	11.43
SHIPPING WEIGHT (lb.)	7.75
SHIPPING WEIGHT (kg)	3.40
USCG APPROVAL	n/a
BRACKET	Plastic Strap Bracket Included

This information is subject to change without notice. Badger Fire Protection disclaims any liability for any errors or misinterpretations of the information contained therein. Contact Badger Fire Protection for your local distributor for assistance.

Distributed by:

Badger Fire Protection
8767 Seminole Trail
Ruckersville, VA 22968
Tel.: 434.964.3200 • Fax: 434.964.3202
www.badgerfire.com

SS B-003
All Rights Reserved.

Mar 2017

