

SPECIALTY EXTINGUISHERS

33 Gal. Direct Pressure Premix Foam

The Model 630 contains a premixed alcohol resistant AFFF ATC foam which is highly effective on Class B fuel fires and a penetrating and wetting agent on fires involving Class A materials. Excellent when used as a vapor suppressant on fuel spills to prevent ignition. Quality hardware throughout including the unique agent cylinder fabricated entirely of stainless steel - no interior coatings are necessary. Model 630 meets NFPA 418 requirements for H-1 category helicopter pad protection.



FEATURES:

- Stainless Steel Collars
- Chrome Plated Brass Fill Caps
- Brass Hose Fittings
- Live Swivels on Discharge Valve
- Heavy Duty Steel Cylinder, Carriage, Hose Rack
- UL/ULC Bilingual (English/Spanish) Nameplates with Bar Code
- Large instruction pictogram
- DOT/TC Nitrogen Cylinder with Quick Opening Brass Valve
- 5 Year Warranty

Test Standards:

CAN/ULC S554 & ANSI/UL 8
CAN/ULC S508 & ANSI/UL 711

SPECIFICATIONS	33 GAL. FOAM
MODEL NUMBER	630
AGENT TYPE	AFFF ATC
UL & ULC RATING	20A:160B
CAPACITY (GAL. / LITER)	33 / 124.91
SHIPPING WT. (LBS. / KG)	390 / 176.88
HEIGHT (IN. / CM)	57 / 144.78
WIDTH (IN. / CM)	34 / 86.36
DEPTH (IN. / CM)	39 / 99.06
DISCHARGE TIME (SEC.)	60
DISCHARGE RANGE (FT. / M)	30 - 40 / 9.1 - 12
OPERATING TEMP. (F / C)	+35° to 120° / +2° to +49°
NITROGEN CYLINDER (CU. FT. / LITER)	23 / 651.29
SAFETY BURST DISC RANGE (PSI / kPa)	400 - 500 / 2760 - 3450
HOSE LENGTH (FT. / M)	50 / 15.2
HOSE DIAMETER (IN. / CM)	1 / 2.54
WHEELS [STEEL] (IN. / CM)	36 X 6 / 91.44 X 15.24
USCG APPROVED	YES

Available Options:

- Optional 36" x 6" wheels with non-sparking rubber treads
- Fill Cap with Pressure Indicator

50 & 100 lb. CARBON DIOXIDE

Large volume CO₂ protection provided in either 50 or 100 lb. (2 - 50 lb. cylinders) wheeled extinguishers. Rugged construction and easy to operate with a "quick opening" 'T' handle valve and horn mounted shut-off valve. A logical choice in areas where a Class B:C non-contaminating agent is required and where hand portable extinguishers do not provide adequate protection.

FEATURES:

- Heavy Duty Steel Carriages
- Quick Opening Brass Valve
- Squeeze Grip Chrome Plated Discharge Valve
- Reinforced Wire Braided Hose and Shock Resistant Horn to Reduce Static Electricity
- Brass Hose Fittings
- UL/ULC Bilingual (English/Spanish) Nameplates with Bar Code
- Large instruction pictogram
- DOT/TC Cylinder with Quick Opening Brass Valve
- Clean, Non-Contaminating Odorless Gas
- 5 Year Warranty



SPECIFICATIONS	CARBON DIOXIDE	
MODEL NUMBER	333	334
AGENT TYPE	CARBON DIOXIDE	
UL & ULC RATING	20B:C	
CAPACITY (LB. / KG)	50 / 22.7	100 / 45.4
SHIPPING WT. (LB. / KG)	257 / 116.6	461 / 209.3
HEIGHT (IN. / CM)	47 / 119.5	
WIDTH (IN. / CM)	23 / 58.4	
DEPTH (IN. / CM)	48 / 122	
DISCHARGE TIME (SEC.)	44+-5	74 +-8
DISCHARGE RANGE (FT. / M)	10 - 15 / 3.04 - 4.57	
OPERATING TEMP. (F / C)	-22° to +120° / -30° to +49°	
HOSE LENGTH (FT. / M)	40 / 12.1	
HOSE DIAMETER (IN. / CM)	.25 / .635	
WHEELS [FULL PNEUMATIC] (IN. / CM)	16 X 4 / 40.64 X 10.16	
USCG APPROVED	YES	

Available Options:

- 100 lb. Stationary Design - Model 335
- Semi-Pneumatic Wheels

Test Standards:

CAN/ULC S503 & ANSI/UL 154
CAN/ULC S508 & ANSI/UL 711

DESIGNED AND ASSEMBLED IN USA