

NITROGEN CYLINDER OPERATED

125/150, 300/350 lb. Direct Pressure - ABC, REGULAR, PURPLE K Dry Chemical

125 lb. ABC & Purple K and 150 lb. Regular Direct Pressure extinguishers utilize a 23 ft³ nitrogen cylinder with a "quick opening brass valve" to pressurize and completely discharge the agent cylinder. The compact size and 16" semi-pneumatic tires allow easy maneuvering and operation by one person, through narrow doorways and aisles. A 4" stainless steel fill opening with rugged chrome plated brass cap makes servicing easier. For large hazards choose the 300 lb. ABC or Purple K or 350 lb. Regular Direct Pressure extinguishers with a "quick opening" 55 ft³ nitrogen cylinder. They provide quality and economical fire protection, large volume capacity for extra high hazard areas with single person transport and operation. The 36" X 6" wide steel wheels make movement possible in sandy or soft soil.



FEATURES:

- Stainless Steel Collars
- Chrome Plated Brass Fill Caps
- Brass Hose Fittings
- Live Swivels on Discharge Valve
- Heavy Duty Steel Cylinder, Carriage, Hose Rack
- Lifting Eyes
- UL/ULC Bilingual (English/Spanish) Nameplates with Bar Code
- Large instruction pictogram
- DOT/TC Nitrogen Cylinder with Quick Opening Brass Valve
- 6 Year Warranty



Available Options:

- 100 ft. Hose
- Fill Cap with Pressure Indicator

Test Standards:

CAN/ULC S504 & ANSI/UL 299
CAN/ULC S508 & ANSI/UL 711

Available Options:

- 36" x 6" wheels with non-sparking rubber treads
- 100 ft. hose
- Fill Cap with Pressure Indicator

SPECIFICATIONS	125/150 LB. DRY CHEMICAL			300/350 LB. DRY CHEMICAL		
MODEL NUMBER	450	451	452	491	492	493
AGENT TYPE	ABC	REGULAR	PURPLE K	ABC	REGULAR	PURPLE K
UL & ULC RATING	30A:240B:C	240B:C	320B:C	40A:320B:C	320B:C	320B:C
CAPACITY (LBS.)	125 / 57	150 / 68	125 / 57	300 / 136.07	350 / 158.75	300 / 136.07
SHIPPING WT. (LBS.)	335 / 152	360 / 163	335 / 152	743 / 337.01	793 / 359.69	743 / 337.01
HEIGHT (IN. / CM)	45 / 115			57 / 144.78		
WIDTH (IN. / CM)	24 / 61			34 / 86.36		
DEPTH (IN. / CM)	36 / 92			39 / 99.06		
DISCHARGE TIME (SEC.)	52	60	53	60	70	67
DISCHARGE RANGE (FT. / M)	30 - 40 / 9 - 12					
OPERATING TEMP. (F / C)	-65° to +120° / -54° to +49°					
NITROGEN CYLINDER (CU. FT. / LITER)	23 / 651			55 / 1557.43		
SAFETY BURST DISC RANGE (PSI / kPa)	400 - 500 / 2760 - 3450					
HOSE LENGTH (FT. / M)	50 / 15.24					
HOSE DIAMETER (IN. / CM)	.75 / 1.90			1 / 2.54		
WHEELS [SEMI-PNEUMATIC / STEEL] (IN. / CM)	16 X 4 / 40.64 X 10.16			36 X 6 / 91.44 X 15.24		
USCG APPROVED	YES					

DESIGNED AND ASSEMBLED IN USA