EXIT SIGNS







Illumination:

- Ultra-bright, energy efficient, long-life LED's
- · Available with red or green lens

Electrical:

- Dual 120/277 VAC
- Charge rate/power "ON" LED indicator light and pushto-test switch for mandated code compliance testing
- 4.8V maintenance-free, rechargeable Ni-Cad battery (4NICDC), except AC only model
- Internal solid-state transfer switch automatically connects the internal battery to LED board/light pipe for minimum 90-minute emergency illumination
- Solid-state, two-rate charger recharges battery in 24 hours

Mounting:

- EZ-snap universal mounting canopy included for top or end mount (5½" x 4½")
- Universal knockout pattern on back plate for wall mount

Housing:

- Injection molded, engineering-grade, 5VA flameretardant, high-impact-resistant thermoplastic
- Available in white or black housings
- EZ-snap out chevron directional indicators
- Compact, low-profile design
- Universal double face

Warranty/Listing:

- Five year warranty on all electronics and housing
- UL listed in accordance with UL924
- UL listed for damp locations (32°F 120°F)

Dimensions:





Available with Self Diagnostic (SDT) feature or AC only model

P/N	DESCRIPTION
LED1	Exit Sign - LED, White Housing, Red Lens w/Battery Back-Up
LED6	Exit Sign - LED, White Housing, Green Lens w/Battery Back-Up
LED1B	Exit Sign - LED, Black Housing, Red Lens w/Battery Back-Up
LEDAC	Exit Sign - LED, AC Only, White Housing, Red Lens
LED1SDT	Exit Sign - LED, Self-Diagnostic Testing, White Housing, Red Lens w/Battery Back-Up



Heiser Logistics • 35 North Street, Suite 50 • Canandaigua, NY 14424 Telephone: 800.828.9638 • Fax: 800.782.2937 • Email: sales@heiserusa.com www.heiserusa.com